Roland VersaWorks®

Roland Professional Print Management Software Included



Roland VersaWorks® supports Adobe® Illustrator®, CoreIDRAW® and other popular design software packages. Choose from a wide variety of layout functions including scaling, cropping, rotating, auto layout and tiling to optimise your print media. VersaWorks also features Roland Color System Libraries for accurate colour matching of traditional and metallic colours, and variable data printing which allows you to efficiently create a series of signs, labels and name badges in which the text and graphics change from one print to the next.

		Adobe PostScript 3			
Roland VersaWorks	System Requirements				
Operating system	Windows® 7 Professional/Ultimate (32/64-bit); Windows Vista® Business/Ultimate (32/64-bit); Windows® XP Professional Service Pack 2 or later (32/64-bit)				
CPU	Core™ 2 Duo, 2.0 GHz or faster recommended				
RAM	2 GB or more recommended				
Video card and monitor	A resolution of 1,280 x 1,024 or more recommended				
Free hard-disk space	40 GB or more recommended				
Hard-disk file system	NTFS format				
Optical drive	DVD-ROM drive				
'Roland VersaWorks™ is a 32-bit	application, which runs on 64-bit Windows® with WoW64 (Windows 32-bit on Windows 64-bit).				
Application softwar	e compatible with Cutting and Print&Cut				
Adobe® Illustrator® 10, CS, CS2, CS3, CS4, CS5 / CorelDRAW® 11, 12, X3, X4, X5					

R-Works Easy-To-Use Roland Design Software Included

R-Works* allows you to immediately start designing graphics for the BN-20, even if you do not have any design software of your own. With R-Works, you can quickly import commercially-available stock photos or personal photos taken with a digital camera. Create original layouts with text and graphics for custom T-shirts, labels and decals. * R-Works does not correspond to a white ink loading type.




R-Works System Requirements Windows[®] 7 Professional /Ultimate (32-bit); Windows Vista[®] Business/Ultimate (32-bit); Windows[®] XP Professional Service Pack 2 or later (32-bit)

Specifications			Options	Model	Description	
Printing technology		Piezoelectric inkjet		ESL3-MG	Magenta, 220 cc	
Media	Width	150 to 515 mm (5.9 to 20.3 in.)			Yellow, 220 cc	
	Thickness	Maximum 1.0 mm (39 mil) with liner, for printing		ESL3-CY	Cyan, 220 cc	
		Maximum 0.4 mm (16 mil) with liner and 0.22 mm (9 mil) without liner, for cutting	ECO-SOL MAX Ink	ESL3-BK	Black, 220 cc	
	Roll outer diameter	Maximum 150 mm (5.9 in.)		ESL3-MT	Metallic silver, 220 cc	
	Roll weight	Maximum 6 kg (13.2 lbs.)			White, 220 cc	
	Core diameter	76.2 mm (3 in.) or 50.8 mm (2 in.) SL-CL (Cleaning liquid, 1 pc.		
Printing/cutting width*1		Maximum 480 mm (18.9 in.)	Blade	ZEC-U5022	For thick, reflective and fluorescent vinyl, 2pcs.	
Ink cartridges	Type and capacity	Roland ECO-SOL MAX (220 cc cartridge)	Blade holder	XD-CH3	Blade holder with blade extension adjuster, mad	
		Five colours (cyan, magenta, yellow, black, and metallic silver or white) or				
	Colours	Four colours (cyan, magenta, yellow, and black)				
Printing resolution (dpi)		Maximum 1,440 dpi	-			
Cutting blade	Туре	Roland CAMM-1 series compatible				
	Blade offset	0.25 mm (9 mil)		1000		
Cutting speed		10 to 150 mm/s				

Printing resolution (dpi)		Maximum 1,440 dpi		
Cutting blade	Туре	Roland CAMM-1 series compatible		
cutting blade	Blade offset	0.25 mm (9 mil)		
Cutting speed		10 to 150 mm/s		
Blade force		30 to 300 gf		
Software resolution (when cutting)		0.025 mm/step		
Distance accuracy (when printing) *2 *3		Error of less than ±0.3% of distance travelled, or ±0.3 mm, whichever is greater		
Distance accuracy (when cutting) *2 *4		Error of less than ±0.4% of distance travelled, or ±0.3 mm, whichever is greater		
Repetition accuracy (when cutting) *2 *5		±0.1 mm or less		
Alignment accuracy for printing and cutting *2 *6		±0.5 mm or less		
Alignment accuracy for printing and cutting		Error of less than ±0.5% of distance travelled, or		
when reloading media *2 *7		±3 mm, whichever is greater		
Print heater *8		Temperature: 35°C (95°F)		
Connectivity		USB (compliant with Universal Serial Bus Specification Revision 2.0)		
Power-saving function / Power requirements		Automatic sleep feature / AC 100 to 240 V ±10 %, 1.5 A, 50 / 60 Hz		
Power consumption	During operation	Approx. 90 W		
Fower consumption	Sleep mode	Approx. 5.5 W		
Acoustic noise level	During operation	62 dB (A) or less		
Acoustic hoise level	During standby	42 dB (A) or less		
Dimensions / Weight		995 (W) x 585 (D) x 291 (H) mm (39.2 (W) x 23 (D) x 11.5 (H) in.) / 35 kg (79.4 lbs.)		
Environmental	Power on	Temperature: 20 to 32°C (68 to 90°F), humidity: 35 to 80%RH (no condensation)		
Linvironmental	Power off	Temperature: 5 to 40°C (41 to 104°F), humidity: 20 to 80%RH (no condensation)		
Included items		Power cord, USB cable, blade, blade holder, Roland Software Package,		
		Software RIP (Roland VersaWorks), User's Manual, etc.		

*1 The length of printing or cutting is subject to the limitations of the program. *2 Using Roland specified media, loaded correctly, temperature: 25°C (77°F), humidity: 50 %RH, all pinch rollers are used, 25 mm or more for both right and left margins and 35 mm or more form torn margin, excluding expansion or contraction of the media, and all correction and adjustment functions of this machine have been made properly. *3 Using Roland specified media, pint travel of 1m. *4 Using Roland specified media, and travel of 1m. *5 Range for assured repetition accuracy. Length 1,000 mm *6 Provided that media length is under 1,000 mm. Excluding possible shift caused by expansion/contraction of the media and/or by reloading the media. *7 Using Roland specified media, data size: 1,000 mm in the media-feed direction, 480 mm in the carriage-movement direction. No lamination. Automatic detection of crop marks at 4 points when media is reloaded. Excludes the effects of skewed movement and d expansion and contraction of the media. *8 Warm. up is required after power up. This may require 5 to 20 minutes, depending on the operating environment. The preset temperature may fail to be reached 35°C (95°F) depending on the ambient temperature and media with



Roland reserves the right to make changes in specifications, materials or accessories without notice. Your actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland dealer for details. No guarantee or warranty is implied other than expressly stated. Roland shall not be liable for any incidential or consequential damages, whether foreseeable or not, caused by defects in such products. Adobe, PostScript 3 and the PostScript to loop are trademarks of Adobe Systems Incorporated. All other trademarks are the property or their respective owners. Roland DG Corp. has licensed the MMP technology from the TPL Group.



AUTHORISED DEALER:

www.rolanddg.co.uk

Optional Stand PNS-24

Imagine. **Roland**







Add Unlimited Value To Your Business with the Versatile VersaSTUDIO

The VersaSTUDIO BN-20 enables you to launch a stream of new businesses from your desktop. This compact professional inkjet can produce durable graphics for outdoor applications, and its Print&Cut capabilities allow you to produce labels and decals with ease. Metallic silver ink is perfect for creating striking effects, and white ink is ideal for transparent or coloured media applications. In short, the versatility of the VersaSTUDIO BN-20 adds unlimited potential to produce creative applications and add value to your business.

