

SUPERFLEX EVOLUTION®

XP3019 - 50cm wide

Superflex Evolution takes things to the next level due to it's hotmelt formular reducing the pressing time to only 5 seconds. The tacky backing makes intricate designs quick and simple to produce onto various textile compositions which includes Nylon.

A4 samples are available free of charge upon request, for larger samples 1m rolls are available to purchase.

STEP BY STEP

STEP 1

Cut your design in mirror image. Film blade required.

STEP 2

Weed away any excess material.

STEP 3

Place transfer face down onto the garment with the transparent backing on top and press for 5 seconds at 140°C. (20 second press when printing onto Nylon).

STEP 4

Remove the transparent backing hot.

ACCREDITATIONS



CLASS 1

CLASS 2

Fluorescent colours



DURABILITYMICRONSFINISHTACKPEELPU OR PVC60°C75MattHighHotPU

PRODUCT INFORMATION

SIZE: 50cm wide x 1m, 5m, 20m rolls

CUTTING FORCE: Film blade (0.25) from 30gf *

TRANSFER LAYERING: No

SUITABLE FOR

COTTON

POLYESTER

POLY/COTTON

UNCOATED NYLON

TRANSFER SETTINGS	
TIME	5 seconds (For Nylon press for 20 seconds)
TEMP	140°C
PRESSURE	Medium
PEEL	Hot or Cold

CARE INFORMATION

WASH UP TO 60°C (Up to 40°C for Nylon)

DO NOT DRY CLEAN

CAN BE TUMBLE DRIED

CAN BE IRONED

STORAGE (Store vertically in a dry room between 15-30°C)

* All force testing has been undertaken using a NEW blade on a Roland GS24. The force will increase with the age of the blade, therefore always test prior to use.

PLEASE NOTE: The sellers and manufacturers maximum obligation shall be to replace any product that has been proven to be defective. Neither the seller nor the manufacturer of Superflex Evolution shall be liable for any injury direct or consequential, arising out of the use of, or inability to use this range. Superflex Evolution has been tested using Kustom Kit garments, when applying to other garment brands esults may vary, testing prior to purchase is recommended.

