AIR CLAM X







Z.I. de Pastabrac - 11260 ESPERAZA - FRANCE
Tél. +33 (0)4 68 74 05 89 - Fax +33 (0)4 68 74 24 08
E-mail : contact@sefa.fr - Web-site : www.sefa.fr

Technical characteristics

Plates Sizes 400 x 500 mm

Weight 61 kg

Pressure 102 gr/cm² / 0.1 bars

204 gr/cm² / 0.2 bars 408 gr/cm² / 0.4 bars

510 gr/cm² / 0.5 bars

Max Temperature 220°C

Power Supply 230 V

Electric Power 2500 W

Amperage 11 A

Settings



Electronics developped by Sefa.

Accurate and fast regulation (PID control) for a wide range of heat transfer products: Flex, lock,

sublimation, screen printing transfer.

Advanced electronics

Double timer (main + pre-heat) 2 counters,

3 programmes Power save mode Fonction stop cycle

From 0 to 570 sec (precision +/-1%). From 0 to 220°C (précision +/- 1%).

Temperature rising time from 0 to 180°C: 15 mn.

Accessories



Table TAB-PRO2 EXT:

Strong support table, perfect for Sefa presses.

With retractable extensions on

each side.



Junior plates kit

(On request)



Cover HOU-50:

Hight temperature resistant **NOMEX®**

Softer and gliding surface to easily put your textile on the plate.

Protecting the foam as well.

Dimensions

